



Miniature circuit breaker 230 V 10kA, 1+N-pole, C, 13A

Model	
product brand name	SENTRON
product designation	Miniature circuit breaker
General technical data	
number of poles	2
design of pole	1P+N
tripping characteristic class	C
mechanical service life (switching cycles) typical	10 000
overvoltage category	III
degree of pollution	2
Voltage	
type of voltage of the operating voltage	AC
insulation voltage (U <sub>i</sub> )	250 V
<ul style="list-style-type: none"> <li>with single-phase operation at AC rated value</li> </ul>	
Supply voltage	
supply voltage at AC rated value	230 V
value range of the supply voltage frequency	50/60 Hz
operating voltage	72 V
<ul style="list-style-type: none"> <li>at DC rated value maximum</li> </ul>	
Protection class	
protection class IP	IP20, with connected conductors
Switching capacity	
switching capacity current	10 kA
<ul style="list-style-type: none"> <li>according to EN 60898 rated value</li> <li>according to IEC 60947-2 rated value</li> </ul>	10 kA
energy limitation class	3
Dissipation	
power loss [W] for rated value of the current at AC in hot operating state per pole	1.5 W
Current	
operational current	13 A
<ul style="list-style-type: none"> <li>at 30 °C rated value</li> <li>at 40 °C rated value</li> <li>at 45 °C rated value</li> <li>at 55 °C rated value</li> <li>at AC rated value</li> </ul>	12.01 A 11.44 A 10.35 A 13 A
suitability for operation	Residential buildings/infrastructure
Product details	
product feature	Yes
<ul style="list-style-type: none"> <li>halogen-free</li> </ul>	

• sealable	Yes
• silicon-free	Yes
product extension installable supplementary devices	Yes

### Connections

connectable conductor cross-section solid	
• minimum	0.75 mm <sup>2</sup>
• maximum	25 mm <sup>2</sup>
connectable conductor cross-section stranded	
• minimum	0.75 mm <sup>2</sup>
• maximum	25 mm <sup>2</sup>
connectable conductor cross-section finely stranded with core end processing	
• minimum	0.75 mm <sup>2</sup>
• maximum	25 mm <sup>2</sup>
tightening torque with screw-type terminals	
• minimum	2.5 N·m
• maximum	3 N·m

### Mechanical Design

height	90 mm
width	36 mm
depth	76 mm
installation depth	70 mm
number of modular width units	2
mounting position	any
net weight	280 g

### Environmental conditions

ambient temperature during operation	
• minimum	-25 °C
• maximum	55 °C
ambient temperature during storage	
• minimum	-40 °C
• maximum	75 °C

### Certificates

reference code	
• according to EN 61346-2	F
• according to IEC 81346-2	F

### General Product Approval

Declaration of Conformity



[Confirmation](#)



[Miscellaneous](#)



### Declaration of Conformity



EG-Konf.

### Test Certificates

[Miscellaneous](#)

### other

[Miscellaneous](#)

[Environmental Conformations](#)

### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SL4513-7>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SL4513-7>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SL4513-7](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SL4513-7)

CAX-Online-Generator





