



Miniature circuit breaker 230 V 6kA, 1-pole+N, B, 6A

Model	
product brand name	SENTRON
product designation	Miniature circuit breaker
General technical data	
number of poles	2
design of pole	1P+N
tripping characteristic class	B
mechanical service life (switching cycles) typical	10 000
overvoltage category	III
degree of pollution	2
Voltage	
type of voltage of the operating voltage	AC
insulation voltage (Ui)	
• with single-phase operation at AC rated value	250 V
Supply voltage	
supply voltage at AC rated value	230 V
value range of the supply voltage frequency	50/60 Hz
operating voltage	
• at DC rated value maximum	72 V
Protection class	
protection class IP	IP20 with distribution board cover
Switching capacity	
switching capacity current	
• according to EN 60898 rated value	6 kA
energy limitation class	3
Current	
operational current	
• at 30 °C rated value	6 A
• at 40 °C rated value	0.93 A
• at 45 °C rated value	5.4 A
• at AC rated value	6 A
suitability for operation	Residential buildings/infrastructure
Product details	
product feature	
• halogen-free	Yes
• sealable	Yes
• silicon-free	Yes
product extension installable supplementary devices	No
Connections	
connectable conductor cross-section solid	

• minimum • maximum	0.75 mm ² 25 mm ²
connectable conductor cross-section stranded	
• minimum • maximum	0.75 mm ² 25 mm ²
connectable conductor cross-section finely stranded with core end processing	
• minimum • maximum	0.75 mm ² 25 mm ²
tightening torque with screw-type terminals	
• minimum • maximum	2.5 N·m 3 N·m

Mechanical Design

height	90 mm
width	36 mm
depth	76 mm
installation depth	70 mm
number of modular width units	2
mounting position	any
net weight	215 g

Environmental conditions

ambient temperature during operation	
• minimum • maximum	-25 °C 45 °C
ambient temperature during storage	
• minimum • maximum	-40 °C 75 °C

Certificates

reference code	
• according to EN 61346-2 • according to IEC 81346-2	F F

General Product Approval

other

[Confirmation](#)



[Miscellaneous](#)

[Environmental Confirmations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SL6506-6YA>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SL6506-6YA>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SL6506-6YA

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



